| SAN ANTONIO INTL (SAT)(KSAT) 7 N UTC-6(-5DT) N29°32.04' 809 B LRA Class I, ARFF Index C NOTAM FILE SAT RWY 04-22: H8505X150 (CONC-GRVD) S-95, D-190, 2S-175, 2D-270 PCN 91 R/B/W/T HIRL CL | W98º28.14′ |
|--|--------------|
| RWY 04: MALS. PAPI(P4R)—GA 3.0° TCH 79′. RVR-T Pole. | |
| 0.3% down. | |
| RWY 22: REIL. PAPI(P4L)—GA 3.0° TCH 85'. RVR-R 0.5% up. | |
| RWY 13R-31L: H8502X150 (CONC-GRVD) S-95, D-190, 2D-270 | /~~~ (A) (A) |
| PCN 86 R/B/W/T HIRL CL | |
| RWY 13R: ALSF2. TDZL. PAPI(P4L)-GA 3.0° TCH 75'. RVR-TMR | 1. 32 B |
| RWY 31L: MALSR. PAPI(P4L)-GA 3.0° TCH 82'. RVR-TMR Bidg. | 1 1 |
| RWY 13L-31R: H5519X100 (ASPH) S-59, D-120 PCN 61 F/C/W/T | \land |
| MIRL | |
| RWY 13L: REIL. PAPI(P4L)—GA 3.0° TCH 40'. | |
| RWY 31R: REIL. PAPI(P4L)—GA 3.0° TCH 60'. | |
| RUNWAY DECLARED DISTANCE INFORMATION | |
| RWY 04: TORA-8505 TODA-8505 ASDA-8505 LDA-8505 | |
| RWY13L:TORA-5519 TODA-5519 ASDA-5519 LDA-5519 | |
| RWY 13R: TORA-8502 TODA-8502 ASDA-8502 LDA-8502 | |
| RWY 22: TORA-8505 TODA-8505 ASDA-8505 LDA-8505 | |
| RWY 31L:TORA-8502 TODA-8502 ASDA-8502 LDA-8502 | |
| RWY 31R:TORA-5519 TODA-5519 ASDA-5519 LDA-5519 | |
| SERVICE: S4 FUEL 100LL, JET A OX 1, 2, 3, 4 | |
| AIRPORT REMARKS: Attended continuously. Numerous flocks of birds invof ar | |
| arpt dur VFR. Rwy 13L-31R not avbl part 121 for air carrier ops. Work | |
| twys and ramps areas at various times. Aerodrome all sfc work in progre | |
| clsd to acft with wingspan greater than 171'. Use only with 24 hr PPR | |
| for acft powering back from terminal gates. Acft taxiing on Rwy 04 nort | |
| | |



g ops aprx 17 miles northwest of eduled maintenance on and along nfo ctc ops 210-413-4928. Arpt 0-413-4928. PPR with arpt ops k for hold short to Rwy 31L. Acft taxiing on Twy N southwest bound look for hold short to Rwy 31R. Twy Z clsd to acft with wingspan greater than 118'. The following twys are not avbl for acft 59,000 lbs or over: Twy A and Twy J north of Rwy 13R-31L, Twy M and Twy P, Twy H northwest of Twy Z and Twy E east of Rwy 04-22. Twy R west of Twy D clsd to acft over 270,000 lbs. Compass deviation may occur at the northwest portion of Twy R due to rebar reinforced conc bridge located under the twy. Inner ramp taxilane east of Terminal A is clsd to acft with wingspan greater than 118' exc for acft crossing the inner ramp to gates A1 to A5. Inner taxilane north of Terminal A and B is clsd to acft with wingspan greater than 118'. Acft at Terminal A and B advise gnd ctl prior to push. Twy L clsd northbound. Twys L and B clsd to acft with wingspans greater than 118' exiting Rwy 31L. Twy D non-movement area from Twy N to 500' west of Twy N. Twy R btn apch end Rwy 13L and Twy D clsd to acft wingspan more than 135'. Twy S btn apch end Rwy 13L and Rwy 13R-31L clsd to acft wingspan more than 135'. A barricaded pavement elev chg exists along the eastern side of the west ramp. Frequent rubber accumulation northwest 2500' Rwy 13R-31L. NS ABTMT Noise sensitive areas exist on all sides of the arpt, at pilots discretion climb as quickly and quietly as safely possible on departure and use consideration when flying over populated areas by minimizing flt and high pwr settings. Engine run-ups are permitted btn 1200-0500Z‡. Gnd run-up enclosure avbl 24 hrs. Terminal Gates A1, A5, A6, A7 and A8 use only with PPR call ops 210-413-4928. C130 and C141 type acft shall park on west ramp to clear cstms. All intl general aviation clear U.S. Cstms at south cstms ramp, call U.S. CSTMS 210-821-6965 upon arr. Flight Notification Service (ADCUS) available. NOTE: See Special Notices-Continuous Power Facilities AIRPORT MANAGER: 210-207-3450 WEATHER DATA SOURCES: ASOS (210) 805-5583 HIWAS 116.8 SAT. WSP. COMMUNICATIONS: D-ATIS 118.9 UNICOM 122.95 RC0 122.3 (SAN ANGELO RADIO) $(\mathbb{B} \text{ app/dep con } 128.05 (091^{\circ}-140^{\circ}) 125.1 (271^{\circ}-359^{\circ}) 124.45 (360^{\circ}-090^{\circ}) 118.05 (141^{\circ}-270^{\circ})$ TOWER 119.8 GND CON 121.9 CLNC DEL 126.7 CPDLC (LOGON KSAT) AIRSPACE: CLASS C svc ctc APP CON VOR TEST FACILITY (VOT) 110.4 RADIO AIDS TO NAVIGATION: NOTAM FILE SAT.

(H) VORTACW 116.8 SAT Chan 115 N29°38.64' W98°27.68' 176° 6.6 NM to fid. 1160/8E. HIWAS.
ALAMO NDB (LOM) 368 AN N29°36.46' W98°34.18' 126° 6.9 NM to fid.
ILS/DME 109.7 I–SAT Chan 34 Rwy 04. Class IB. Unmonitored.
ILS/DME 110.9 I–ANT Chan 46 Rwy 13R. Class IIE. LOM ALAMO NDB. DME also serves Rwy 31L.
ILS/DME 110.9 I–IZR Chan 46 Rwy 31L. Class IA. DME also serves Rwy 13R.