

ST PAUL DOWNTOWN HOLMAN FLD (STP)(KSTP) P (ARNG) 1 S UTC-6(-5DT) N44°56.08'

TWIN CITIES

W93°03.62'

H-21, L-121, 141, A

705 B TPA—1905(1200) LRA NOTAM FILE STP

IAP, AD

Rwy 14-32: H6491X150 (ASPH-GRVD) S-83, D-111, 2D-197 HIRL

Rwy 14: MALSR. PAPI(P4R)—GA 3.0° TCH 50'. RVR-TR Thld dspld 343'. Road.

Rwy 32: REIL. PAPI(P4L)—GA 3.0° TCH 40'. RVR-TR Thld dspld 382'. Trees.

Rwy 13-31: H4004X150 (ASPH) S-97, D-135, 2S-175, 2D-228

HIRL

Rwy 13: PAPI(P4L)—GA 3.0° TCH 40'.

Rwy 31: REIL. PAPI(P4L)—GA 3.0° TCH 45'.

Rwy 09-27: H3642X100 (ASPH) S-12.5, 2S-175 MIRL

Rwy 09: Tree.

Rwy 27: PAPI(P4R)—GA 4.0° TCH 40'. Rgt ftc.

RUNWAY DECLARED DISTANCE INFORMATION

Rwy 14:

LDA-6148

Rwy 32:

LDA-6109

ARRESTING GEAR/SYSTEM

Rwy 14: EMAS

Rwy 32: EMAS

SERVICE: S4 FUEL 100LL, JET A OX 1, 2 LGT When twr clsd, to

increase ints and ACTIVATE MALSR Rwy 14, HIRL Rwy 14-32 and Rwy 13-31, MIRL Rwy 09-27, PAPI Rwy 13, Rwy 27, and Rwy 31, and REIL Rwy 31—CTAF. PAPI Rwy 14, and Rwy 32 operates continuously. Rwy 13 PAPI unusable byd 4° right of course, inside .5 NM. Rwy 14 PAPI unusable byd 8° left of course. Arpt beacon on west edge of arpt.

MILITARY—A-GEAR Rwy 14 EMAS 280' x 162'. Rwy 32 EMAS 225' x 162'. **FUEL** J8(Mil), A (1100-0500Z‡ Mon-Fri; 1300-0400Z‡ Sat-Sun; C651-227-8108, OT PN 4 hr), (NC-100LL)

AIRPORT REMARKS: Attended continuously. Fuel: JET A Idg fee, ctc FBO. Arpt CLOSED to acft over 100,000 lbs. Deer, birds and wildlife on and invof arpt. Complex airport geometry. Verify correct compass heading prior to departure. PPR acft over 100,000 lbs, ctc arpt manager. For noise abatement procedures, www.macnoise.com/pilots. Acft please follow voluntary noise abatement procedures. Rwy 14 is calm wind rwy when twr clsd. When using Rwy 27 or Rwy 31, hazardous river tfc may exist. Southeast arrivals and departures avoid tfc pattern ops at South St. Paul arpt 164° 5 NM at and blo 1720' MSL. Twy A clsd between Twy A3 and Twy A4 except for wingspan less than 101'. Expect helicopter ops on Twy A invof the ctrl twr, north to the apch end of Rwy 14. Twy B clsd between MN jet ramp and Twy A (southern corner) except for wingspan less than 72' due to flood wall obstacle. Flight Notification Service (ADCUS) avbl. Ldg fee.

AIRPORT MANAGER: 651-224-4306

WEATHER DATA SOURCES: ASOS (651) 298-1410 LAWRS.

COMMUNICATIONS: CTAF 119.1 ATIS 118.35 UNICOM 122.95

Ⓡ **MINNEAPOLIS APP/DEP CON** 121.2

ST PAUL TOWER 119.1 (1200-0400Z‡ Mon-Fri, 1300-0400Z‡ Sat-Sun)

GND CON 121.675 **CLNC DEL** 121.675

MINNEAPOLIS APCH CONTROL CLNC DEL 121.675 (0400-1200Z‡ Mon-Fri, 0400-1300Z‡ Sat-Sun)

ARNG OPS 126.2 347.7

AIRSPACE: CLASS D svc 1200-0400Z‡ Mon-Fri, 1300-0400Z‡ Sat-Sun other times CLASS E.

VOR TEST FACILITY (VOT) 114.4

RADIO AIDS TO NAVIGATION: NOTAM FILE PNM.

GOPHER (H) VORTACW 117.3 GEP Chan 120 N45°08.74' W93°22.39' 127° 18.4 NM to fld. 877/6E. **HIWAS.**

HOPEY NDB (MHW) 400 PPI N44°52.40' W92°56.52' 303° 6.2 NM to fld. 1013/3E. NOTAM FILE STP.

ILS/DME 111.5 I-VKG Chan 52 Rwy 14. Class IB. Unmonitored when twr clsd. LOC unusable 9° right of course.

Glideslope unusable 4° left or right of course. LOC unusable byd 6° left of course.

ILS/DME 111.5 I-BAO Chan 52 Rwy 32. Class IA. DME unusable blo 3,500' byd 25° left of course. Unmonitored when twr clsd.

COMM/NAV/WEATHER REMARKS: Emerg frequency 121.5 not avbl at twr.

